SPE

Model 555 Flexible Catheter Probe





- Conversion chart supplied with each probe to allow use with 400 series compatible monitors
- Glass encapsulated bead thermistor sensor
- Extremely fast time response
- · High sensitivity to temperature change
- 1/4" phone plug connector
- 0.7 mm diameter flexible sensor
- CE Marked for global sales, but not for medical patient use

DESCRIPTION

400-series compatible (with use of conversion chart) flexible catheter probe

FEATURES APPLICATIONS

- Conversion chart supplied with each probe to allow use with 400 series compatible monitors
- Standard ¼" phone plug connector
- 0.7 mm diameter flexible sensor

- Laboratory measurements liquid immersion
- Research use for animal measurements


PERFORMANCE SPECS

Parameter	Units	Value
Resistance @ 25°C (including lead resistance)	Ohms	2252.4
Tolerance 0°C to 70°C (using supplied conversion chart)	°C	± 0.1
Beta Value 25/85 (using supplied conversion chart)	K	3976
Tolerance on Beta Value (using supplied conversion chart)	%	0.4
Typical response time in stirred fluid	Seconds	< 1
Insulation Resistance (Min. of 100Mohms for 1 Sec.)	Volts	500
Liquid immersion with 15VDC applied	Ohms	> 15Meg



Model 555 Flexible Catheter Probe

MECHANICAL DETAILS



RESISTANCE V TEMPERATURE TABLE

Note: 400 series response curve shown is compatible with conversion chart supplied with each probe.

Temp °C K-Ohms	
0	7.3554
1	6.9894
2	6.6444
3	6.3194
4	6.0114
5	5.7194
6	5.4444
7	5.1834
8	4.9374
9	4.7034
10	4.4824
11	4.2734
12	4.0744
13	3.8864
14	3.7084
15	3.5394
16	3.3784
17	3.2264
18	3.0814
19	2.9444
20	2.8144
21	2.6904
22	2.5724
23	2.4604
24	2.3544

Temp °C	K-Ohms
25	2.2524
26	2.1564
27	2.0644
28	1.9774
29	1.8944
30	1.8154
31	1.7394
32	1.6674
33	1.5994
34	1.5334
35	1.4714
36	1.4124
37	1.3554
38	1.3014
39	1.2494
40	1.2004
41	1.1524
42	1.1074
43	1.0644
44	1.0234
45	0.9842
46	0.9466
47	0.9106
48	0.8762
49	0.8432

Temp °C	K-Ohms
50	0.8117
51	0.7815
52	0.7526
53	0.7249
54	0.6983
55	0.6729
56	0.6485
57	0.6252
58	0.6028
59	0.5813
60	0.5607
61	0.5409
62	0.5219
63	0.5037
64	0.4862
65	0.4694
66	0.4533
67	0.4378
68	0.4229
69	0.4086
70	0.3949



Model 555 Flexible Catheter Probe

ORDERING INFORMATION

Part Number	Description	Ω @25°C	MOQ
050555	555 PROBE 0.7-MM CATHETER	2252.4	5

^{*} For quantities less than Minimum Order Quantity – contact distribution

NORTH AMERICA EUROPE ASIA

Measurement Specialties, Inc. 910 Turnpike Road Shrewsbury, MA 01545 Tel: 1-508-842-0516

Fax: 1-508-842-0342

Sales email:

temperature.sales.amer@meas-spec.com

Measurement Specialties, Inc Ballybrit Business Park Galway Ireland Tel: +353-91-753238 Fax: +353-91-770789

Sales email:

temperature.sales.emea@meas-spec.com

Measurement Specialties (China) Ltd. No. 26 Langshan Road Shenzhen High-Tech Park (North) Nanshan District, Shenzhen 51807 China

> Tel: +86 (0) 755 33305088 Fax: +86 (0) 755 33305099

Sales email:

temperature.sales.asia@meas-spec.com

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.